

PAS-CAB010A | 1.0 SQ MM 2 Core Armoured Speaker Cable



Key features

- High-Quality Transmission: Delivers clear and accurate audio signals.
- Armoured Construction: Galvanized iron layer for durability.
- Audiophile Quality: Crystal-clear sound transmission.
- Tinned Conductors: Enhanced conductivity and oxidation resistance.
- Twisted Cores: Minimizes crosstalk and interference.
- Rugged Design: Suitable for direct burial or wall installation.
- Versatile Applications: Perfect for auditoriums, schools, malls and industries.
- Convenient Lengths: Available in 100 to 500-meter coils.

Product Overview

The Macsys PAS-CAB010A Armored Speaker Cable is designed for exceptional durability and high-quality audio performance. Featuring an armoured construction with a galvanized iron layer, this cable can withstand challenging conditions, making it ideal for both direct burial and wall installation. It delivers crystal-clear sound with precise transmission thanks to its tinned conductors and twisted cores, which reduce crosstalk and interference. The cable's high-quality transmission ensures that audio signals remain clear and accurate. Suitable for a wide range of applications, including auditoriums, schools, and malls, the Macsys PAS-CAB010A is available in convenient lengths from 100 to 500 meters, accommodating various installation needs with ease.

Technical Specification

Featues	Detail
Product Category	Armoured Speaker Cable
Conductors	Bare Copper, Aluminium Tinned Multi-Thread Copper
Conductor Type	1.0 Sq mm Twisted Pair Cable, Identical color code for secure connection
Core	2 core
Cable Type	Oxygen-Free Type Cable
Jacket Material	PVC
Temperature Rating	70°C
Insulation Resistance	10,000 MΩ x m Min. at DC 125V, 20°C
Conductor Resistance	13.70 Ω/Km @ 20°C
Lengths Available	100, 200, 500 meters (Custom lengths available upon request)
Additional Features	Twisted cores, tinned conductors, rugged design, galvanised iron armouring



for more detail reach us @ www.macsystemtech.com | write us on : contact@macsys.com

©2024 Macsys

Macsys reserve rights to introduce modifications without notice. Product images are for illustrative purposes only, the actual product may vary. Warranty policy applies as described on our website.

