

PAS-IBS40W | Box Speaker with Twitter



Key features

- Indoor wall-mounted box speaker designed for clear and pleasant sound.
- Multiple power tap settings for 70V, 100V, and 8Ω systems.
- Robust housing made of HIPS with a powder-coated iron mesh grill.
- Easy installation with a bracket and adjustable angle.
- Wide frequency response for versatile sound delivery.
- Comes in two color options: white and black.

Product Overview

The PAS-IBS40W is a wall-mounted indoor box speaker providing clear, pleasant sound quality suitable for public spaces and meeting rooms. It features a frequency response of 80–20KHz and a sensitivity of 88dB ±3dB at 1 meter.

The speaker supports multiple power taps for 70V, 100V, and 8Ω installations, allowing flexible power usage up to 40W. Its durable housing is made from HIPS with a powder-coated iron mesh grill, and it includes a 6.5-inch woofer paired with a 1-inch silk dome tweeter. The unit is designed for easy installation with a mounting bracket and adjustable angle, available in both white and black finishes. Operating in temperatures from -25°C to 55°C.

Technical Specification

Feature	Details
Frequency Range	80–20KHz
Sensitivity	88dB ±3dB (1m/1W)
Power Rating	40W
Power Tap Settings	5W/10W/20W/40W @ 100V; 2.5W/5W/10W/20W/40W @ 70V; 40W @ 8Ω
Input Line Voltage	100V / 70V
Housing Material	HIPS
Front Grill	Powder Coated Iron Mesh
Speaker Components	6.5" Woofer + 1" Silk Dome
Available Colors	White / Black
Weight	3.34kg
Dimensions (W x H x D)	216mm × 299mm × 196mm
Operating Temperature	-25°C to 55°C
Certification	CE, RoHS Compliance



for more detail reach us @ www.macsys.tech | write us on : contact@macsys.com

©2024 Macsys

Macsys reserve rights to introduce modifications without notice. Product images are for illustrative purposes only, the actual product may vary. Warranty policy applies as described on our website.

