

PAS-PLSB20W | Bi-directional Projector Speaker



Key features

- IP55-rated, weather-resistant construction
- Robust aluminum housing for enhanced durability
- Integrated 20W transformer for flexible installation
- Bi-directional sound projection
- Wide 320° horizontal coverage
- Supports both 10W and 20W power settings

Product Overview

The PAS-PLSB20W is a Bi-directional Projector Speaker 100v@20W designed for wall or corridor installation, offering reliable outdoor or indoor performance with an IP55 rating. Housed in a steady aluminum enclosure, it features a bi-directional sound projection and integrated 20W transformer for versatile use. It supports 10W and 20W power configurations, with a sensitivity of 92dB and a maximum SPL of 103dB.

The frequency response ranges from 110Hz to 15KHz, ensuring clear audio reproduction for voice and background music applications. With a 320-degree horizontal coverage and dual 6.5-inch full-range drivers, the PAS-PLSB20W provides extensive sound distribution. Its compact dimensions and 3.4kg weight make it suitable for a range of professional audio installations.

Technical Specification

Feature	Details
Model	PAS-PLSB20W
Power Handling	10/20W
Rated Input Power	5/10W
Sensitivity	92dB
Maximum SPL	103dB
Frequency Range	110Hz~15KHz
Horizontal Coverage	320 degree
Dimensions (Diameter x Length)	Dia 170×252mm
Mounting Application	Wall or corridor
Material	Aluminum
Weight	3.4Kg
Color	White
Speaker Units	6.5" ×2 full range
Certifications	CE, RoHS compliance



for more detail reach us @ www.macsystemtech.com | write us on : contact@macsys.com

©2024 Macsys

Macsys reserve rights to introduce modifications without notice. Product images are for illustrative purposes only, the actual product may vary. Warranty policy applies as described on our website.

